
Products
– Control & Lightings

SLC600-L Lighting Switch









Description

The Lighting Switch SLC600-L is designed to control your device On/Off remotely and schedule for automatic switching. Each gang can be controlled separately.

Main Features

- ZigBee 3.0 compliant
- Works with any standard ZigBee Hub
- 1~4 gang on/off
- Remote on/off control
- Enables scheduling for automatic switching
- Available in 3 colors
- Customizable text

Main Specifications

Wireless Connectivity	
ZigBee	• 2.4GHz IEEE 802.15.4
ZigBee Profile	• ZigBee 3.0
RF Characteristics	• Operating frequency: 2.4GHz • Range outdoor/indoor: 100m / 30m • Internal PCB Antenna
Physical Specifications	
Operating Voltage	• 100~250 Vac 50/60 Hz
Power consumption	• < 1 W
Max. Load Current	• 10A (All gangs)
Operating environment	• Indoor • Temperature: -20 ℃ ~+50 ℃ • Humidity: ≤ 90% non-condensing
Dimension	• 86 Type Wire Junction Box • Product size: 92(L) x 92(W) x 35.4(H) mm • In-wall size: 63.3(L) x 61.9(W) x 22.4(D) mm • Thickness of front panel: 13mm
Compatible system	• 3-wire Lighting Systems
Weight	• 145g
Mounting Type	• In-wall mounting • CN standard